



SANY

Pauta de Mantenimiento

SANY SW978K

HH		Cant	1RAS 50H	250H	500H	750H	1000H	1250H	1500H	1750H	2000H	2250H	2500H	2750H	3000H	3250H	3500H	3750H	4000H
Tipo	Material																		
Filtros	Filtro aceite motor flt sw978k	2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro separador combust flt sw978k	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Pre filtro combust flt sw978k	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro combustible flt sw978k	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Conj filtro aire motor flt sw978k	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro aire acond acs syl956	1			✓		✓		✓		✓		✓		✓		✓	✓	
	Filtro retorno tanque flt syl956	1					✓				✓				✓			✓	
	Filtro hidraulico succion flt syl956	1						✓				✓				✓		✓	
	Filtro respiradero hyd sy35-500/sw936	1						✓				✓			✓			✓	
	Filtro linea alta presion flt syl956	1						✓				✓			✓			✓	
Correas	Elemento filtro transmision flt sw978k	1					✓				✓			✓				✓	
	Correa alternador eng sw978k	1									✓							✓	
	Correa compresor acs sw978k	1									✓							✓	
LUBRICANTE RECOMENDADO																			
Aceites	Motor diesel	24	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Grasa	4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Transmision	45	✓				✓				✓				✓			✓	
	Eje frontal *	27					✓				✓				✓			✓	
	Eje trasero*	27					✓				✓			✓				✓	
	Sistema hidraulico	220									✓							✓	
	Refrigerante	45									✓							✓	

Notas: 1) En maquinas que trabajen en condiciones severas, con martillo hidráulico se deberá reducir el intervalo de mantenimiento hidráulico en 50%

2) Ser recomienda una tolerancia de ± 20 horas en el cambio de aceite y filtro de motor

3) En cada mantención, se debe verificar el estado de los filtros, si se detecta que estos se saturan antes del cambio programado, será necesario modificar el intervalo señalado.

4) En cada cambio de correas revisar tensor, dado que deberíamos cambiarno a las 4000 horas.