



**SANY**

# Pauta de Mantenimiento

SANY SY500H

HH		Cant	1RAS 50H	250H	500H	750H	1000H	1250H	1500H	1750H	2000H	2250H	2500H	2750H	3000H	3250H	3500H	3750H	4000H
Tipo	Material																		
Filtros	Filtro aceite motor flt sy215/245/305	2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro separador agua/combust flt sy500	1			✓		✓		✓		✓		✓		✓		✓		
	Filtro separador/combus sy500/sy365	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro combustible elemento flt sy75	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro combustible flt sy135/305/365	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro aire exterior motor flt sy305-500	1			✓		✓		✓		✓		✓		✓		✓		
	Filtro aire interior motor flt sy305-500	1			✓		✓		✓		✓		✓		✓		✓		
	Filtro aire cabina ext flt sy75-500	1					✓				✓				✓				
	Filtro aire int cab flt sy135-500	1																	
	Filtro hidraulico retorno flt sy500	1						✓				✓			✓			✓	
	Filtro hidraulico succion flt sy500	1						✓				✓			✓			✓	
	Filtro hidr retorno tanque flt sy500	1						✓				✓			✓			✓	
Correas	Filtro respiradero hyd sy35-500/sw936	1					✓				✓			✓				✓	
	Filtro malla piloto flt sy135/215/245	1					✓				✓			✓				✓	
Correas	Correa compresor acs sy500	1									✓							✓	
	Correa ventilador	1									✓							✓	
<b>LUBRICANTE RECOMENDADO</b>																			
Aceites	Motor diesel	50	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Grasa	4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Motor de giro	14					✓				✓			✓				✓	
	Mando final izq	10						✓				✓			✓			✓	
	Mando final der	10						✓				✓			✓			✓	
	Sistema hidráulico	400									✓							✓	
	Refrigerante	60									✓							✓	

Notas: 1) En maquinas que trabajen en condiciones severas, con martillo hidráulico se deberá reducir el intervalo de mantenimiento hidráulico en 50%

2) Ser recomienda una tolerancia de ± 20 horas en el cambio de aceite y filtro de motor

3) En cada mantención, se debe verificar el estado de los filtros, si se detecta que estos se saturan antes del cambio programado, será necesario modificar el intervalo señalado.

4) En cada cambio de correas revisar tensor, dado que deberíamos cambiario a las 4000 horas.