



SANY

Pauta de Mantenimiento

SANY SYL956HS5

HH		Cant	1RAS 50H	250H	500H	750H	1000H	1250H	1500H	1750H	2000H	2250H	2500H	2750H	3000H	3250H	3500H	3750H	4000H
Tipo material																			
	Filtro aceite motor flt syl956h5	1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Prefiltro combust flt (fs20124) syl956	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro separador combust flt syl956	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro combustible cartucho flt syl956	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro aire externo motor flt syl956	1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Filtro aire interior motor flt syl956	1			✓		✓		✓		✓		✓		✓		✓		
Filtros	Filtro aire acond acs syl956	1			✓		✓		✓		✓		✓		✓		✓		
	Filtro retorno tanque flt syl956	1						✓					✓					✓	
	Filtro hidraulico succion flt syl956	1						✓				✓			✓			✓	
	Filtro respiradero hyd sy35-500/sw936	1						✓				✓						✓	
	Filtro malla piloto flt sy135/215/245	1						✓				✓			✓			✓	
	Filtro linea alta presion flt syl956	1						✓				✓			✓			✓	
	Filtro transmision flt syl956	1						✓				✓			✓			✓	
Correas	Correa compresor acs syl956	1										✓						✓	
	Correa alternador eng syl956	1									✓							✓	
LUBRICANTE RECOMENDADO																			
	Motor diesel	24	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Grasa	4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Aceites	Transmision	20	✓					✓				✓			✓			✓	
	Eje frontal *	27	✓					✓				✓						✓	
	Eje trasero*	27	✓					✓				✓			✓			✓	
	Sistema hidraulico	220										✓						✓	
	Refrigerante	45										✓						✓	

Notas: 1) En maquinas que trabajen en condiciones severas, con martillo hidráulico se deberá reducir el intervalo de mantenimiento hidráulico en 50%

2) Ser recomienda una tolerancia de ± 20 horas en el cambio de aceite y filtro de motor

3) En cada mantención, se debe verificar el estado de los filtros, si se detecta que estos se saturan antes del cambio programado, será necesario modificar el intervalo señalado.

4) En cada cambio de correas revisar tensor, dado que deberíamos cambiarlo a las 4000 horas.